


2600 SKYPARK DRIVE TORRANCE, CALIFORNIA 90509 AREA CODE 213 · 775-3181 · 326-8110



BLIN ASS	BOLT EMBLY	BE312 CORE BOLT								BB571 SLEEVE								BB415GA EXPANDER				SUGGESTED HOLE PREPARATION		PROTRUSION AFTER INSTALLATION	
FIRST DASH NUMBER	NOMINAL DIAMETER	FIRST DASH NUMBER	RECESS	A DIA.	D DIA.	н	P ₁	Ť (REF)	THREAD	FIRST DASH NUMBER	A ₁ DIA.	B GRIP RANGE 0-3/4	B GRIP RANGE 13/16-11/16	B GRIP RANGE 11/6-15/6	B GRIP RANGE 1 ¹¹ / ₁₆ -2 ¹ / ₄	D ₁ DIA.	н	DASH NUMBER	D ₂ DIA.	L (LENGTH)	THREAD	HOLE DIA.	CORE BOLT INSTALLATION TORQUE	p ·	D ₃ DIA. (REF)
-6	3/16	-6	Phillips #1	. 2514 . 2466			. 239	.304	5-40UNJC-3A	-6	.315	. 250	. 265	330		.213 .210	.065	-6	. 194	. 184	5-40 UNJC-3B	. 208	10 14 IN. LBS.	. 239	.260
				-													-								
	-																								

BB312 CORE BOLT

GENERAL NOTES: 1. Concentricity: Head to "D" diameter within .005 FIR.

2. Complete threads shall begin within two thread pitches maximum. Two thread pitch maximum may consist of incomplete thread and extrusion angle.

3. "H" is dimensioned from maximum "D" diameter.

MATERIAL: A-286 alloy per AMS5731 or AMS5735.

HEAT TREAT: 95,000 psi shear minimum.

CODE:

First dash number of core bolt indicates sleeve nominal diameter in 32nds. Second dash number indicates mean

assembly grip length (thickness of work) in 16ths.

EXAMPLE: BB312-6-12 = 3/16 nominal sleeve diameter, 3/4 mean assembly grip length.

BB571 SLEEVE

GENERAL NOTES: 1. Concentricity: Hole to "D" diameter within .005 FIR.

Head to "D1" diameter within .010 FIR.

MATERIAL: A-286 alloy per AMS5731.

① HEAT TREAT: Anneal per AMS5736.

CODE: First dash number indicates nominal diameter of sleeve in 32nds for which the BB571 is the oversized replacement.

Second dash number indicates mean assembly grip

length (thickness of work) in 16ths.

EXAMPLE: BB571-6-12 = 3/16 nominal sleeve diameter, 3/4 mean assemble grip length.

BB415GA EXPANDER

GENERAL NOTES: 1. Threads per MIL-S-8879.

MATERIAL: A-286 alloy per AMS5731 or AMS5735.

HEAT TREAT: 110,000 psi shear minimum.

FINISH: Silver plate per AMS2411, .0002-.0004 thick. Dash number indicates nominal diameter of Blind Bolt

Assembly in 32nds.

EXAMPLE: BB415GA-6 = 3/16 nominal diameter Blind Bolt Assembly.

BB569 BOLT ASSEMBLY

First dash number indicates nominal diameter of Blind Bolt Assembly in 32nds. Second dash number indicates mean assembly grip length (thickness of

work) in 16ths.

EXAMPLE: BB569-6-12

3/4 Mean Assembly Grip Length 3/16 Nominal Diameter Blind Bolt Assembly

Blind Bolt Assembly which includes: BB312 Core Bolt, BB569 Sleeve, and BB415GA Expander

U.S. Patents 2,789,619; 2,946,208; 2,959,999. Foreign patents granted and pending.

BLIND BOLT™ ASSEMBLY

PROTRUDING HEAD STYLE A-286 ALLOY

SPECIAL OVERSIZE FOR P & W

Funderson (1) 5-24-77 © 1977, Hi-Shear Corporation

BB569