

**Nut, Lightweight, 6AL-4V Titanium,
Hexagonal, Self-locking,
Up to 2nd pin shank oversize
(for use with HI-LITE™ pins)**

STR24




FIGURE 1: CONFIGURATION

NOTES:

UNLESS OTHERWISE SPECIFIED

- I. **Units** Dimensions and tolerances are in inches (millimeters).
Loads are in Lbf (Newton).
Dimensions apply after finish, before application of solid film lube.
- II. **Surface texture** As per ASME B46.1 before coating.
- R_a max. = $\sqrt[125]{\quad}$ (3,2 μ m).
- Tool mark or distortion permissible in the locking area.
- III. **Thread** UNJF-3B as per SAE AS8879, except diameter code 5 (UNJC-3B).
Go thread gage penetration shall be 3/4 of one revolution minimum after thread lock.

Technical Center	Written by	Signature	Approved by	Signature	Date	Issue
PAGE 1/6	F. CARINGELLA		J. LO		2019-07-24	C

**Nut, Lightweight, 6AL-4V Titanium,
 Hexagonal, Self-locking,
 Up to 2nd pin shank oversize
 (for use with HI-LITE™ pins)**

STR24

1. APPLICATION

This product standard specifies the dimensions, tolerances and properties of a STARLITE™ titanium nut, for use in aerospace application at a maximum operating temperature of 450°F (232°C).
 The nut is designed to fit HI-LITE™ pins (with short threads and cylindrical shank), nominal diameter, first and second oversize. It can be used to fasten structures with a sloped surface from 0° to 1°.

2. REQUIREMENTS

Table 1: Material, finish and identification

PART	FINISH CODE	MATERIAL	HEAT TREAT	FINISH	LUBRICATION
Nut	TA	Titanium alloy 6AL-4V as per chemistry of AMS4928, AMS4965, or AMS4967	Solution treated and aged per AMS-H-81200 unless material procured to AMS4965	N/A	Surface preparation per Hi-Shear Ti-Shield III and HI-KOTE™ 2 solid film lube per Hi-Shear Spec. 292, and cetyl alcohol lube per Hi-Shear Spec. 305
	HK			HI-KOTE™ 4 NC aluminum coating per Hi-Shear Spec. 397	N/A
Washer	WT	Commercial pure titanium per ASTM B 265, ASTM B 348. Minimum yield 25 KSI.	N/A	Titanium surface treatment anodize per Hi-Shear Spec. 306, Type I, color brown	Cetyl alcohol lube per Hi-Spec. 305

**Nut, Lightweight, 6AL-4V Titanium,
Hexagonal, Self-locking,
Up to 2nd pin shank oversize
(for use with HI-LITE™ pins)**

STR24

Table 2 : Dimensions and tolerances

Øcode (1/32")	THREAD UNJF-3B	ØA REF	ØC REF	ØD		H REF	M REF	W ⁽²⁾ ± .002 (± 0,05)
				MIN	MAX			
5	.1640-32 ⁽¹⁾	.334 (8,48)	.248 (6,30)	.174 (4,41)	.180 (4,57)	.234 (5,94)	.089 (2,26)	.217 (5,51)
6	.1900-32	.389 (9,88)	.282 (7,17)	.229 (5,81)	.233 (5,91)	.248 (6,30)	.084 (2,13)	.247 (6,27)
7	.2160-28	.442 (11,23)	.317 (8,06)	.244 (6,20)	.250 (6,35)	.263 (6,68)	.090 (2,29)	.278 (7,06)
8	.2500-28	.514 (13,06)	.352 (8,94)	.291 (7,40)	.297 (7,55)	.283 (7,19)	.086 (2,18)	.309 (7,85)
10	.3125-24	.616 (15,65)	.424 (10,77)	.354 (9,00)	.360 (9,15)	.327 (8,31)	.091 (2,31)	.372 (9,45)
12	.3750-24	.728 (18,49)	.566 (14,38)	.417 (10,60)	.423 (10,75)	.370 (9,40)	.091 (2,31)	.497 (12,62)
14	.4375-20	.816 (20,73)	.636 (16,16)	.480 (12,20)	.486 (12,35)	.423 (10,74)	.097 (2,46)	.559 (14,20)
16	.5000-20	.926 (23,52)	.707 (17,96)	.543 (13,79)	.549 (13,94)	.463 (11,76)	.097 (2,46)	.619 (15,72)
18	.5625-18	1.044 (26,52)	.779 (19,79)	.606 (15,38)	.612 (15,53)	.525 (13,34)	.100 (2,54)	.682 (17,32)
20	.6250-18	1.101 (27,97)	.883 (22,43)	.668 (16,96)	.674 (17,11)	.521 (13,23)	.100 (2,54)	.773 (19,63)
24	.7500-16	1.301 (33,05)	1.062 (26,98)	.794 (20,16)	.800 (20,31)	.604 (15,34)	.105 (2,67)	.930 (23,62)
28	.8750-14	1.496 (38,00)	1.203 (30,56)	.919 (23,35)	.925 (23,50)	.683 (17,35)	.112 (2,84)	1.054 (26,77)
32	1.0000-12	1.686 (42,83)	1.347 (34,22)	1.045 (26,55)	1.051 (26,71)	.786 (19,96)	.120 (3,09)	1.180 (29,97)

- (1) Dia. code 5: UNJC-3B thread as per SAE AS8879
(2) Dimensions apply before application of locking feature

**Nut, Lightweight, 6AL-4V Titanium,
Hexagonal, Self-locking,
Up to 2nd pin shank oversize
(for use with HI-LITE™ pins)**

STR24

Table 3: Tensile strength, mass and wrench size

Øcode (1/32")	THREAD UNJF-3B	Min. Axial Tensile Strength ⁽²⁾ Lbf (N)	Mass ⁽³⁾ Lb / 1000 parts (Kg / 1000 parts)	Wrench Size (inch)
5	.1640-32 ⁽¹⁾	2 302 (10 240)	1.270 (0,576)	7/32
6	.1900-32	2 788 (12 400)	1.673 (0,759)	1/4
7	.2160-28	3 822 (17 000)	2.301 (1,044)	9/32
8	.2500-28	5 283 (23 500)	3.044 (1,381)	5/16
10	.3125-24	8 302 (36 930)	4.818 (2,185)	3/8
12	.3750-24	13 039 (58 000)	8.968 (4,068)	1/2
14	.4375-20	19 008 (84 550)	12.874 (5,840)	9/16
16	.5000-20	25 509 (113 470)	17.769 (8,060)	5/8
18	.5625-18	29 012 (129 050)	23.312 (10,574)	11/16
20	.6250-18	32 013 (142 400)	27.001 (12,247)	25/32
24	.7500-16	46 906 (208 650)	44.253 (20,073)	15/16
28	.8750-14	63 223 (281 230)	62.290 (27,254)	1-1/16
32	1.0000-12	85 654 (381 010)	89.026 (40,382)	1-3/16

(1) Dia. code 5: UNJC-3B thread as per SAE AS8879

(2) Mechanical properties apply at room temperature

(3) With captive washer

Tensile value is valid for nut only.

See pin standards for pin strengths.

Lower strength (fastener or nut) determines system strength.

**Nut, Lightweight, 6AL-4V Titanium,
Hexagonal, Self-locking,
Up to 2nd pin shank oversize
(for use with HI-LITE™ pins)**

STR24

3. DESIGNATION

STR24 TAWT ()

Dia. code number in 1/32nds inch

Nut and washer finish code (table 1)

Basic part number

Example:

STR24TAWT16: STR24 nut for HI-LITE™ pins fastener systems, titanium alloy 6AL-4V coated with solid film lube coating HI-KOTE™ 2 and cetyl alcohol lube, with anodized titanium washer with cetyl alcohol lube, dia. code ½ inch.

4. MARKING

Manufacturer symbol and basic part number on the flange area (except Ø5/32": manufacturer symbol only).

Marking shall be oriented and positioned approximately as shown in Figure 1, arrangement optional.

5. QUALIFICATION AND ACCEPTANCE

The nuts shall meet all the inspection requirements of LISI AEROSPACE Qualification and Acceptance Specification STR-QA05, except locking torque, breakaway tests, to be done on performed, using preload releasing fixture.

Technical
Center

Issue

**Nut, Lightweight, 6AL-4V Titanium,
 Hexagonal, Self-locking,
 Up to 2nd pin shank oversize
 (for use with HI-LITE™ pins)**

STR24

Issue	Date	Modifications	Justification
A	2018-12-13	Changed Drawing Format: From Hi-Shear Corporation Format to Technical Center	Incorrect initial release
B	2019-04-01	Updated AMS2801 To AMS81200	Spec AMS2801 does not allow for standard industry practice with respect to loading
C	2019-07-24	1) Section 4: WAS: Marking shall be positioned as indicated on Figure 1.	1) Allow for arrangement of marking at manufacturing option

Technical
Center

Issue