

FIRST DASH NO.	PIN NOM DIA	A DIA MAX	A' DIA MIN	B REF	D DIA		TD DIA	F	H REF	M GAGE PROT.	R RAD	V GAGE DIA	Z MAX	S CHAMFER REF	THREAD MODIFIED	SOCKET			
					WITHOUT COATING OR SOLID FILM	AFTER COATING OR SOLID FILM										W HEX	T DEPTH MIN	T1 DEPTH MAX	Y DIA
24	49/64	1.3000	1.251	.905	.7646 .7641	.7646 .7636	.7430 .7370	.012	.222	.0776 .0716	.050 .040	1.1124 1.1122	.022	1/16 x 37°	.7500-16 UNJF-3A	.3185 .3150	.300	.523	.398 .378
28	57/64	1.5091	1.461	1.010	.8896 .8891	.8896 .8886	.8680 .8610	.014	.257	.0694 .0622	.050 .040	1.3440 1.3438	.022	5/64 x 37°	.8750-14 UNJF-3A	.3820 .3780	.370	.608	.471 .451
32	1-1/64	1.7201	1.671	1.170	1.0146 1.0141	1.0146 1.0136	.9930 .9860	.014	.292	.0617 .0536	.050 .040	1.5732 1.5730	.022	5/64 x 37°	1.0000-12 UNJF-3A	.5100 .5040	.490	.770	.618 .598

- GENERAL NOTES:**
- Head edge out of roundness shall not exceed "F".
 - Concentricity: Conical surface of head to "D" diameter within .005 FIM.
 - "H" is dimensioned from maximum "D" diameter.
 - Dimensions are in inches and to be met after finish.
 - Surface texture per ASME B46.1.
 - Hole preparation per NAS618.
 - Curved or flat edge manufacturer's option.
 - After February, 21st of 2015, HI-KOTE™ 1 aluminum pigmented coating will be replaced by REACH compliant HI-KOTE™ 1 NC aluminum pigmented coating per Hi-Shear Spec. 294 on fasteners coated in European Union.

MATERIAL: 6AL-4V titanium alloy per AMS4928 or AMS4967 or Bistish Standard 2TA 28.

HEAT TREAT: Anneal per Hi-Shear Spec. 380-1.

- FINISH:**
- [8] HST957AP()-() = HI-KOTE™ 1 aluminum pigmented coating per Hi-Shear Spec. 294, and cetyl alcohol lube per Hi-Shear Spec. 305.
 - [8] HST957AT()-() = HI-KOTE™ 1 aluminum pigmented coating per Hi-Shear Spec. 294.
 - HST957CE()-() = I.V.D. aluminum coating per MIL-DTL-83488, Type II (.00015-.00045 thick), with color black on thread end, and cetyl alcohol lube per Hi-Shear Spec. 305.
 - HST957CF()-() = I.V.D. aluminum coating per MIL-DTL-83488, Type II (.00015-.00045 thick), with color black on thread end.
 - [8] HST957KM()-() = HI-KOTE™ 1 aluminum pigmented coating per Hi-Shear Spec. 294, with color white on thread end, and cetyl alcohol lube per Hi-Shear Spec. 305.
 - [8] HST957KN()-() = HI-KOTE™ 1 aluminum pigmented coating per Hi-Shear Spec. 294, with color white on thread end.
 - HST957VF()-() = Surface coating per Hi-Shear Spec. 306, Type I, color blue, and cetyl alcohol lube per Hi-Shear Spec. 305.


SPECIFICATION: HI-LITE™ Product Specification 380-1.

CODE: First dash number indicates nominal diameter in 1/32nds of the pin which HST957 oversize pin replaces. Second dash number indicates maximum grip in 1/16ths. See Finish note for explanation of code letters.

HOW TO ORDER EXAMPLE:

Pin Part Number
HST957AP24-8
8/16 or 1/2 Maximum Grip Length
3/4 Nominal Diameter Pin
Finish Code
Pin Basic Part Number

THIS AREA OF SPECIAL CONFIGURATION AND COLD WORKING TO MEET PHYSICAL REQUIREMENTS



VIEW A

HI-LITE™ THREAD TRANSITION AREA
SEE SPECIFICATION FOR INSPECTION

"HI-LITE", "HST", AND "HI-KOTE", ARE TRADEMARKS OF HI-SHEAR CORPORATION			
DRAWN BY J. OBISPO	DATE 1990-10-29	TITLE HI-LITE™ PIN 100° FLUSH SPECIAL SHEAR HEAD TITANIUM (ANNEALED) 1/16 GRIP VARIATION, 1/64 OVERSIZE	
APPROVED ANNE BROWN	DATE 1990-10-29	DRAWING NUMBER HST957	
REVISION 6	DATE K. MURKER 2020-04-24	1 OF 1	