




13080021



NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL
 - 1.1. CLIP: C1050 CARBON STEEL, .020 THICK.
 - 1.2. NUT: 4037 ALLOY STEEL.
2. HEAT TREAT
 - 2.1. CLIP: Rc48 MINIMUM
 - 2.2. NUT: Rc32 MINIMUM.
3. FINISH
 - 3.1. CLIP: CADMIUM PLATE PER QQ-P-416 TYPE II, CLASS 2.
"G" CODE : CADMIUM PLATE PER QQ-P-416, TYPE III,
CLASS 2 AND COAT BMS10-11 PER EMPS073.
 - 3.2. NUT: CADMIUM PLATE PER QQ-P-416 TYPE II, CLASS 2.
MOLYBDENUM DISULFIDE DRY FILM LUBRICANT.
4. INSTALLATION HOLE DIA.: .218 MINIMUM.

A	ECN # 6557	8-17-99
ISSUE	DESCRIPTION	DATE
	REVISION	9113-012

NEXT ASSEMBLY	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES DECIMALS FRACTION ANGLES ±.015		DRAWN BY: RAD	DATE: 5-20-91	 THE MONADNOCK COMPANY CITY OF INDUSTRY, CALIFORNIA TITLE: NUT ASSEMBLY, LOCKING, 8-32 SIZE, SPECIAL
	MATERIAL:	NOTED	CHECKED BY: CKT	DATE: 5-29-91	
	HEAT TREAT:	NOTED	APPROVED BY: CKT	DATE: 5-29-91	
	FINAL PROTECTIVE FINISH:	NOTED	APPROVED BY: MFG. ACCEPT:	DATE: 6-5-91	
			CODE IDENT. NO. 60119	SIZE B	DRAWING NUMBER: 13080021
			SCALE: NONE	SALES	SHEET 1 OF 1