

13100056





NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

CLIP: CARBON STEEL NUT: ALLOY STEEL

2. HEAT TREAT:

CLIP: Rc 48 MINIMUM NUT: Rc 40 MINIMUM.

3. FINISH:

CLIP: CADMIUM PLATED PER QQ-P-416, TYPE II, CLASS 1.

NUT: DRY FILM LUBRICANT AND HYDRAULIC FLUID RESISTANCE.

- 4. MOUNTING SHEET THICKNESS: .020-.090.
- 5. NOMINAL EDGE DISTANCE: .290-.380.

FAA-TSO AUTHORIZED PART

Α	ECN # 5103	5-5-95
	ECN # 4768	6-20-94
ISSUE	DESCRIPTION	DATE
	REVISION	•

NEXT ASSEMBLY END ITEM	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES, TOLERANCES DECIMALS FRACTION ANGLES + .01	DRAWN BY: DATE MARK 6-20-94 CHECKED BY: DATE	IN TH	THE MONADNOCK COMPANY CITY OF INDUSTRY, CALIFORNIA				
	MATERIAL: NOTED	RAD 6-24-94 APPROVED BY: DATE C. TANAKA	TITLE:	ASSY	, C	CLIP-ON 1032 SIZE		
	HEAT TREAT: NOTED	6-28-94	1032 3126					
		D. BRETT	CODE INDENT. NO.	SIZE	DRAWING NU	JMBER:		
	FINAL PROTECTIVE FINISH: NOTED	6-24-94 MFG. ACCEPT.: DATE	60119	В	13	100056		
		D.PAUL 6-28-94	SCALE: NONE	S	ALES	SHEET 1 OF 1		