


13400006







NOTES: (UNLESS OTHERWISE SPECIFIED)

MATERIAL: CLIP: NUT: CARBON STEEL ALLOY STEEL

HEAT TREAT: CLIP:

2. 2.1 2.2 RC 46 MINIMUM RC 35 MINIMUM NUT:

FINISH:

3. 3.1 3.2 CLIP: NUT: ZINC PLATED WITH YELLOW CHROMATE ZINC PLATED WITH YELLOW CHROMATE

MECHANICAL PERFORMANCE: APPLIED SEATED TORQUE 50 IN. LBS. MAX. SEATED TORQUE TO FAILURE — 90 IN. LBS. MIN. 4. 4.1 4.2

ISSUE	DESCRIPTION			DATE		
13400006,013 REVISION 9413-				9413-002		

NEXT ASSEMBLY	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES, TOLERANCES DECIMALS FRACTION ANGLES +.010	DRAWN BY: R.A.D.	2-8-94			NOCK COMPANY			
		CHECKED BY:	DATE						
	MATERIAL: NOTED	R.A.D.	3-1-94	TILE: CLIP-NUT ASSEMBLY,					
	NOTED	APPROVED BY:	1/1/ 20 0121						
	HEAT TREAT: NOTED	C. TANAKA	3-1-94	STEEL					
		APPROVED BY:	DATE	CODE INDENT, NO.	SIZE	DRAWING NUMBER: 13400006			
	FINAL PROTECTIVE FINISH: NOTED	D.L. BRETT	4-4-94 DATE	60119	В				
		D. PAUL	3-31-94	SCALE: NONE	NONE SALES		SHEET 1 OF	1	